

MSR1510

15 inch RMS 400watt



Specification

- Frequency Response (1W@1m)	: (± 3 dB) : 60Hz~20KHz : (-10dB) : 60Hz~22KHz
- Axial Sensitivity(dB SPL, 1W@1m)	: 99
- Impedance(Ohms) Full Range	: 8
- Power Handling RMS/PROGRAM/PEAK(Watts)	: 400/800/1600W
- Calculated Maximum Output	: Full Range Peak : 124 Full Range Long Term : 118
- Nominal Coverage Angle/-6dB points(Degrees)	: Horizontal : 90, Vertical : 90
- System configuration	: Two-way full range
- Powering	: Passive(LF/HF crossover)
- LF subsystem	: 15"Woofer \times 1
- HF subsystem	: 1.7"HF system protection circuit
- Enclosure Materials	: High intensity 18mm plywood
- Finish/ color	: Water resistant textured black paint
- Connectors	: NL4 Speakon \times 2
- Hardware	: Bottom : SPK Stand Ple Socket, Rear : Suspend Point \times 2 Right/Left : Suspend Point \times 2
- Grille	: Power coated perforated steel, foam backed.
- Weight	: Net. 21.3Kg, Gross. 26Kg
- Dimensions(W \times H \times D)	: 16.9" \times 25.6" \times 15.4"(430mm \times 650mm \times 390mm)